



DGR10-1831-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS


使用参数 Working parameters

MAX. PRESSURE	4.0MPa; (<40Bar)	介质 Fluid	空气 Air	压力 Pressure	1.0MPa;	温度Temperature	-30℃----+120℃	转速 Rotating speed	3000RPM
MAX. SPEED	3500RPM;	水 Water	1.1MPa;		-30℃----+120℃		3500RPM		
TEMPERATURE	-30℃----+120℃	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.							
MEDIA TYPE 介质	water/air								
	冷却水/压缩空气								
备注: 技术参数数据为最大值, 并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.									



旋转接头  
Rotary joint  
E-mail: sddeweier88@163.com

DEWEIER  
德威迩  
www.sddeweier.com



TEL: +86 632 5822778  
TEL: +86 632 5832779

P/N: DGR10-1831-00F