



DGR25-1831-04L





枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	2.5MPa; (<20Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
		空气 Air	1.0MPa:	-30℃----+120℃	1500RPM
MAX. SPEED	3000RPM;	水 Water	1.1MPa:	-30℃----+120℃	2800RPM
TEMPERATURE	-30℃----+120℃	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
MEDIA TYPE 介质	water/air				
	冷却水/压缩空气				
备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					

旋转接头 Rotary joint E-mail: sddeweier88@163.com		 德威迩 www.sddeweier.com
	TEL: +86 632 5822778 TEL: +86 632 5832779	P/N: DGR25-1831-04L