


DGR50-1831-00F





枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	1.6MPa; (16Bar)	介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
MAX. SPEED	750RPM;	空气 Air	1.0MPa;	-30℃----+120℃	500RPM
TEMPERATURE	-30℃----+120℃	水 Water	1.1MPa;	-30℃----+120℃	750RPM
MEDIA TYPE 介质	water/air	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
	冷却水/ 压缩空气				
备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					



	<p>旋转接头</p> <p>Rotary joint</p> <p>E-mail: <a href="mailto:sddeweier88@163.com">sddeweier88@163.com</a></p>	 <p><b>DEWEIER</b></p> <p>德威迩</p> <p><a href="http://www.sddeweier.com">www.sddeweier.com</a></p>
	<p>TEL: +86 632 5822778</p> <p>TEL: +86 632 5832779</p>	<p>P/N: DGR50-1831-00F</p>