


DGR32-1831-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.


技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	2.0MPa; (20Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED	2500RPM;	空气 Air	1.0MPa;	-30℃----+120℃	1500RPM
TEMPERATURE	-30℃----+120℃	水 Water	1.1MPa;	-30℃----+120℃	2500RPM
MEDIA TYPE 介质	water/air	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
	冷却水/ 压缩空气				
备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					



旋转接头
Rotary joint
E-mail: sddeweier88@163.com



www.sddeweer.com



TEL : +86 632 5822778
TEL : +86 632 5832779

P/N:DGR32-1831-00F