



DGR15-1831-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	4.0MPa; (40Bar)	介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
MAX. SPEED	3500RPM;	空气 Air	1.0MPa;	-30℃-----+120℃	2000RPM
TEMPERATURE	-30℃-----+120℃	水 Water	1.1MPa;	-30℃-----+120℃	3000RPM
MEDIA TYPE 介质	water/air	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
	冷却水/ 压缩空气				
备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					



<p>旋转接头 Rotary joint</p> <p>E-mail: sddeweier88@163.com</p>	<p> DEWEIER 德威迩</p>	<p>www.sddeweier.com</p>
<p></p>	<p>TEL: +86 632 5822778 TEL: +86 632 5832779</p>	<p>P/N: DGR15-1831-03R</p>