



06R32-1831-041



枣庄市德威迺机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技 术 参 数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	2.0MPa: (20Bar)	介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
MAX. SPEED	2500RPM;	空气 Air	1.0MPa:	-30℃----+120℃	1800RPM
TEMPERATURE	-30℃----+120℃	水 Water	1.1MPa:	-30℃----+120℃	2500RPM
MEDIA TYPE 介质	water/air	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
	冷却水/压缩空气				
备注: 技术参数数据为最大值, 并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					

<p>旋转接头 Rotary joint E-mail: sddeweier88@163.com</p>	<p> DEWEIER 德威迩 www.sddeweier.com</p>
<p> TEL: +86 632 5822778 TEL: +86 632 5832779</p>	<p>P/N: DGR32-1831-04L</p>