



DGR50-1831-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	1.6MPa; (16Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED	750RPM;	空气 Air	1.0MPa;	-30℃-----+120℃	500RPM
TEMPERATURE	-30℃-----+120℃	水 Water	1.1MPa;	-30℃-----+120℃	750RPM
MEDIA TYPE 介质	water/air	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
	冷却水/压缩空气				
备注：技术参数数据为最大值,并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.					

旋转接头
Rotary joint

E-mail: sddeweier88@163.com

TEL: +86 632 5822778
TEL: +86 632 5832779

DEWEIER
德威迩

www.sddeweier.com

P/N: DGR50-1831-03R