



740-1E81-07890



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	2.0MPa; (20Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED		空气 Air	0.8MPa:	-30℃-----+120℃	1500RPM
TEMPERATURE	2500RPM;	水 Water	1.1MPa:	-30℃-----+120℃	2500RPM
MEDIA TYPE	-30℃-----+120℃	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
介质	water/air				
	冷却水/压缩空气				
备注: 技术参数数据为最大值, 并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					



旋转接头 Rotary joint		DEWEIER 德威迩	
E-mail: sddeweier88@163.com		www.sddeweier.com	
		TEL: +86 632 5822778	P/N: DGR40-1831-04L
		TEL: +86 632 5832779	