

单转盘旋转接头--法兰型

单转盘法兰盘型的主体安装部呈法兰盘形状，降低了整体高度，结构紧凑。

4回路，各回路可独立使用。

2次侧使用Rc1/4接口采用外配管方式连接时，请使用附带的R1/8螺纹堵头塞住板式连接口；

当使用板式连接时，请安装O型圈和R1/4螺纹堵头

Single turntable rotary joint - flange type

The main body mounting portion of the single turntable flange type has a flange shape, which reduces the overall height and is compact.

4 loops, each loop can be used independently.

When using the Rc1/4 interface on the secondary side to connect by e×ternal piping, use the included R1/8 threaded plug to plug the plate connection;

When using a plate connection, install an O-ring and a R1/4 threaded plug





技术参数表 Operating Parameter	
最高压力 Max. pressure:	25MPa;
最高转速 Max. speed:	200RPM.
使用温度 Operating temperature:	-20℃—+80℃
适用介质Fluid used:	液压油/冷却水/压缩空气 Hydraulic oil /water/air
技术参数数据为最大值，不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time;	

德威迩企业官网

德威迩业务号

						Rotary joint	枣庄市德威迩机械科技有限公司
标记	处数	分区	更改文件号	签名	年、月、日		
设计	Andy Yu	2015-10-31	标准化			液压旋转接头	
						阶段标记 / 重量 / 比例	
审核						1:1.5	DRCF0400-Rc1/4''
工艺			批准			共 1 张 第 1 张	