



枣庄市德威迩机械科技有限公司 Dewel Machinery Technology Co., Ltd.				
技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters		
MAX. PRESSURE	32MPa: <320Bar>	介质 Fluid	压力 Pressure	温度Temperature 转速 Rotating speed
MAX. SPEED	300RPM;	空气 Air	2.0MPa:	80℃ 80RPM
TEMPERATURE	-20℃-----+80℃	水 Water	4.0MPa:	80℃ 30RPM
MEDIA TYPE 介质	Hydraulic oil/water/air	液压油 Hydraulic oil	7.0MPa:	80℃ 150RPM
	液压油/冷却水/压缩空气		25MPa:	80℃ 100RPM
备注：技术参数数据为最大值，并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		德威迩公司 DRL01系列旋转接头是一种专门具有多个通道，可连续提供多路介质给低速高压旋转设备的一种旋转接头。 适用于加工中心旋转工作台、旋转平台、卷取机、转炉、大包回转工作台、液压机械及多通路高压控制阀等设备。 DEWEL DRL01 Series are multi-way rotary joints designed to carry multiple media continuously for low-speed and high-pressure equipment. They are used on machining center revolving tables, rotating platforms, coiling machines, converters, ladle turret, hydraulic machinery, multi-way high pressure controller and etc.		



订货编号 Order-No.		
Aluminum 铝壳	Stainless 不锈钢壳	Steel 碳钢
DRL0132-1802-03R	DRL0132-1803-03R	DRL0132-1805-03R
适用介质：压缩空气/液压油等 Applicable medium: compressed air hydraulic oil	适用介质：冷却水/切削液 Applicable medium: water/cutting fluid	适用介质：液压油 Applicable medium: hydraulic oil
多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com		DEWEIER 德威迩 www.sddeweier.com
	TEL : +86 632 5822778 TEL : +86 632 5832779	P/N:DRL0132-G1-1/4"