



DGR15-1801-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd. -30℃-----+120℃

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	4.0MPa; (40Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
		空气 Air	1.0MPa;	-30℃-----+120℃	3000RPM
MAX. SPEED	3500RPM;	水 Water	1.1MPa;	-30℃-----+120℃	3500RPM
TEMPERATURE	-30℃-----+120℃	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
MEDIA TYPE 介质	water/air				
	冷却水/压缩空气				
备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					


备注：技术参数数据为最大值,并不能同时使用;

The technical parameter data is the maximum value and cannot be used at the same time.

旋转接头  
Rotary joint  
E-mail: sddeweier88@163.com

DEWEIER  
德威迩

www.sddeweier.com



TEL: +86 632 5822778  
TEL: +86 632 5832779

P/N: DGR15-1801-00F