



DGR10-1801-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

MAX. PRESSURE	4.0MPa; (40Bar)
MAX. SPEED	3500RPM;
TEMPERATURE	-30℃----+120℃
MEDIA TYPE 介质	water/air 冷却水/压缩空气

备注: 技术参数数据为最大值 并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.

使用参数 Working parameters

介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
空气 Air	1.0MPa;	-30℃--+120℃	2000RPM
水 Water	2.0MPa;	-30℃--+120℃	3500RPM
Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			



旋转接头 Rotary joint E-mail: sddeweier88@163.com		 德威迩 www.sddeweier.com	
		TEL: +86 632 5822778 TEL: +86 632 5832779	P/N: DGR10-1801-03R