



740-1081-05890



枣庄市德威迩机械科技有限公司					
Dewel Machinery Technology Co., Ltd.					
技 术 参 数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	1.6MPa; (16Bar)	介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
		空气 Air	1.0MPa;	-30℃----+120℃	500RPM
MAX. SPEED	750RPM;	水 Water	1.1MPa;	-30℃----+120℃	750RPM
TEMPERATURE	-30℃----+120℃	Double high-precision groove ball bearings for high stability. Balanced mechanical sealing structure for prolonged service life. Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.			
MEDIA TYPE 介 质	water/air				
	冷却水/ 压缩空气				
备注：技术参数数据为最大值, 并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.					

旋转接头  
Rotary joint

E-mail: sddeweier88@163.com

TEL: +86 632 5822778  
TEL: +86 632 5832779

DEWEIER  
德威迩

www.sddeweier.com

P/N:DGR50-1801-04L