


DGR40-1801-03R



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE 2.0MPa; (<20Bar)

MAX. SPEED 2500RPM;

TEMPERATURE -30℃-----+120℃

MEDIA TYPE 介质 water/air
冷却水/压缩空气


介质 Fluid 压力 Pressure 温度 Temperature 转速 Rotating speed

空气 Air 1.0MPa: -30℃-----+120℃ 1500RPM

水 Water 1.1MPa: -30℃-----+120℃ 2500RPM

Double high-precision groove ball bearings for high stability.
Balanced mechanical sealing structure for prolonged service life.
Standard Sic/Carbon Graphite sealing pair for good sealing performance. Optional Sic/Sic, Tungsten carbide/Tungsten carbide and other sealing pairs for strict environment.


备注：技术参数数据为最大值,并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.



旋转接头
Rotary joint
E-mail: sddeweier88@163.com



www.sddeweier.com



TEL: +86 632 5822778
TEL: +86 632 5832779

P/N: DGR40-1801-03R