




DRM0208-1800-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

MAX. PRESSURE	25MPa; <25Bar>
MAX. SPEED	250RPM;
TEMPERATURE	-20℃----+80℃
MEDIA TYPE 介质	Hydraulic oil/water/air 液压油/冷却水/压缩空气

备注：技术参数数据为最大值,并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.

使用参数 Working parameters

介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
空气 Air	1.0MPa:	80℃	200RPM
水 Water	4.0MPa:	80℃	50RPM
液压油 Hydraulic oil	7.0MPa:	80℃	250RPM
	25MPa:	80℃	150RPM

德威迩公司独创的长寿命旋转接头, 供出口数量可选择2、3、4、5、6个接口
DRM uses a professionally developed low-friction seal to achieve low torque and smooth rotation. This joint is a long-life rotary joint that is unique in its combination of high rigidity, high durability and high sealing.



订货编号 Order-No.

Copper 铜壳

Aluminum 铝壳

DRM0208-1801-00F

DRM0208-1802-00F

适用介质: 高压水/液压油等

Applicable medium:
High pressure water
hydraulic oil

适用介质: 压缩空气/液压油等


Applicable medium:
compressed air
hydraulic oil

多通道旋转接头
Multi-Passage Rotary joint

E-mail: sddeweier88@163.com

DEWEIER
德威迩

www.sddeweier.com



TEL: +86 632 5822778
TEL: +86 632 5832779

P/N: DRM0208-1800-00F