




DRM0310-1800-14F



含中央供给口: 3+1

Central supply port: 3+1

枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	25MPa; (<25Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
		空气 Air	1.0MPa:	80℃	200RPM
MAX. SPEED	250RPM;	水 Water	4.0MPa:	80℃	50RPM
		液压油 Hydraulic oil	7.0MPa:	80℃	250RPM
TEMPERATURE	-20℃----+80℃		25MPa:	80℃	150RPM
MEDIA TYPE 介质	Hydraulic oil/water/air	DRM采用专业开发的低摩擦密封件，从而实现了低转矩、顺畅的旋转动作。该接头是兼具了高刚性高耐久性、高密封性的。			
	液压油/冷却水/压缩空气	德威迩公司独创的长寿命旋转接头，供出口数量可选择2、3、4、5、6个接口			
备注：技术参数数据为最大值，并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		DRM uses a professionally developed low-friction seal to achieve low torque and smooth rotation. This joint is a long-life rotary joint that is unique in its combination of high rigidity, high durability and high sealing.			



订货编号 Order-No.

Copper 铜壳

Aluminum 铝壳

DRM0310-1801-14F

DRM0310-1802-14F

适用介质: 高压水/液压油等

Applicable medium:  
High pressure water  
hydraulic oil

适用介质: 压缩空气/液压油等


Applicable medium:  
compressed air  
hydraulic oil

多通道旋转接头  
Multi-Passage Rotary joint

E-mail: sddeweier88@163.com

DEWEIER  
德威迩

www.sddeweier.com



TEL: +86 632 5822778  
TEL: +86 632 5832779

P/N: DRM0310-1800-14F