




DRM0408-1800-14F



含中央供给口：4+1

Central supply port : 4+1



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	25MPa; <25Bar>	介质 Fluid	空气 Air	压力 Pressure	1.0MPa:	温度 Temperature	80℃	转速 Rotating speed	120RPM
MAX. SPEED	250RPM;	水 Water	4.0MPa:	80℃	30RPM				
TEMPERATURE	-20℃----+80℃	液压油 Hydraulic oil	7.0MPa:	80℃	200RPM				
MEDIA TYPE 介质	Hydraulic oil/water/air	25MPa:	80℃	80RPM					
液压油/冷却水/压缩空气		DRM采用专业开发的低摩擦密封件, 从而实现了低转矩、顺滑的旋转动作。此接头是兼具高刚性高耐久、高密封性的。德威迩公司独创的长寿命旋转接头, 供给口数量可选择2、3、4、5、6供给口							
备注: 技术参数数据为最大值, 并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time.		DRM uses a professionally developed low-friction seal to achieve low torque and smooth rotation. This joint is a long-life rotary joint that is unique in its combination of high rigidity, high durability and high sealing.							



订货编号 Order-No.

Copper 铜壳

Aluminum 铝壳

DRM0408-1801-14F

DRM0408-1802-14F

适用介质: 高压水/液压油等

Applicable medium:
High pressure water
hydraulic oil

适用介质: 压缩空气/液压油等


Applicable medium:
compressed air
hydraulic oil

多通道旋转接头
Multi-Passage Rotary joint

E-mail: sddeweier88@163.com

DEWEIER
德威迩

www.sddeweier.com



TEL: +86 632 5822778
TEL: +86 632 5832779

P/N: DRM0408-1800-14F