




DRM0408-1800-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

| | |
|---------------|---|
| MAX. PRESSURE | 25MPa; <25Bar> |
| MAX. SPEED | 250RPM; |
| TEMPERATURE | -20℃----+80℃ |
| MEDIA TYPE 介质 | Hydraulic oil/water/air 液压油/冷却水/压缩空气 |

备注：技术参数数据为最大值,并不能同时使用;
The technical parameter data is the maximum value and cannot be used at the same time.

使用参数 Working parameters

| 介质 Fluid | 压力 Pressure | 温度 Temperature | 转速 Rotating speed |
|-------------------|-------------|----------------|-------------------|
| 空气 Air | 1.0MPa: | 80℃ | 120RPM |
| 水 Water | 4.0MPa: | 80℃ | 30RPM |
| 液压油 Hydraulic oil | 7.0MPa: | 80℃ | 200RPM |
| | 25MPa: | 80℃ | 80RPM |

DRM采用专业开发的低摩擦密封件,从而实现了低转矩、顺滑的旋转动作。此接头是兼具了高刚性高耐久、高密封性的。
德威迩公司独创的长寿命旋转接头,供给口数量可选择2、3、4、5、6供给口
DRM uses a professionally developed low-friction seal to achieve low torque and smooth rotation. This joint is a long-life rotary joint that is unique in its combination of high rigidity, high durability and high sealing.




德威迩企业官网



德威迩业务号

订货编号 Order-No.

| Copper 铜壳 | Aluminum 铝壳 |
|--|--|
| DRM0408-1801-00F | DRM0408-1802-00F |
| 适用介质: 高压水/液压油等 Applicable medium: High pressure water hydraulic oil | 适用介质: 压缩空气/液压油等 Applicable medium: compressed air hydraulic oil |
| 多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com | DEWEIER 德威迩 www.sddeweier.com |
|  TEL: +86 632 5822778 TEL: +86 632 5832779 | P/N: DRM0408-1800-00F |