




DRM0510-1800-38F



含中央供给口: 5+1

Central supply port : 5+1

枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

MAX. PRESSURE	25MPa; <25Bar>	介质 Fluid	空气 Air	压力 Pressure	1.0MPa:	温度 Temperature	80℃	转速 Rotating speed	20RPM
MAX. SPEED	250RPM;	水 Water	4.0MPa:	80℃	15RPM	液压油 Hydraulic oil	7.0MPa:	80℃	80RPM
TEMPERATURE	-20℃----+80℃	25MPa:	80℃	30RPM					
MEDIA TYPE 介质	Hydraulic oil/water/air								
	液压油/冷却水/压缩空气								

备注: 技术参数数据为最大值, 并不能同时使用;  
The technical parameter data is the maximum value and cannot be used at the same time.

DRM uses a professionally developed low-friction seal to achieve low torque and smooth rotation. This joint is a long-life rotary joint that is unique in its combination of high rigidity, high durability and high sealing.



订货编号 Order-No.

Copper 铜壳	Aluminum 铝壳
DRM0515-1801-38F	DRM0515-1802-38F
适用介质: 高压水/液压油等 Applicable medium: High pressure water hydraulic oil	适用介质: 压缩空气/液压油等 Applicable medium: compressed air hydraulic oil
多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com	DEWEIER 德威迩 www.sddeweier.com
TEL: +86 632 5822778 TEL: +86 632 5832779	P/N: DRM0510-1800-38F