






DRM0515-1800-38F



含中央供给口:  $5+1$

Central supply port : 5+1



订货编号 Order-No.	
Copper 铜壳	Aluminum 铝壳
DRM0515-1801-38F	DRM0515-1802-38F
适用介质: 高压水/液压油等 Applicable medium: High pressure water hydraulic oil	适用介质: 压缩空气/液压油等 Applicable medium: compressed air hydraulic oil
<b>多通道旋转接头</b> <b>Multi-Passage Rotary joint</b> E-mail: <a href="mailto:sddeweier88@163.com">sddeweier88@163.com</a>	 <b>DEWEIER</b> 德威迩 <a href="http://www.sddeweier.com">www.sddeweier.com</a>
 TEL: +86 632 5822778 TEL: +86 632 5832779	P/N: DRM0515-1800-38F

枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	25MPa; (25Bar)	分质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED	250RPM;	空气 Air	1.0MPa;	80℃	20RPM
TEMPERATURE	-20℃----+80℃	水 Water	4.0MPa;	80℃	15RPM
		液压油 Hydraulic oil	7.0MPa;	80℃	80RPM
			25MPa;	80℃	30RPM
MEDIA TYPE 介质	Hydraulic oil/water/air	DRM采用专业开发的低摩擦密封件，从而实现了低转矩、顺畅的旋转动作，该接头是兼具了高刚性高耐久性、高密封性的。			
	液压油/冷却水/压缩空气	请参见公司提供的长寿命旋转接头，供货口数量可选择2、3、4、5、6供货口			
备注：技术参数数据为最大值，并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		DRM uses a professionally developed low-friction seal to achieve low torque and smooth rotation. This joint is a long-life rotary joint that is unique in its combination of high rigidity, high durability and high sealing			