



枣庄市德威迩机械科技有限公司					
Dewel Machinery Technology Co., Ltd.					
技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters			
MAX. PRESSURE	32MPa; (320Bar)	介质 Fluid	压力 Pressure	温度 Temperature	转速 Rotating speed
MAX. SPEED	60RPM;	空气 Air	2.0MPa;	80℃	20RPM
TEMPERATURE	-20℃----+80℃	水 Water	4.0MPa;	80℃	20RPM
MEDIA TYPE 介质	Hydraulic oil/water/air	液压油	7.0MPa;	80℃	20RPM
	液压油/冷却水/压缩空气	Hydraulic oil	25MPa;	80℃	15RPM
备注：技术参数数据为最大值,并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		德威迩公司 DRF06 系列旋转接头是一种专门具有多个通道，可连续提供多种介质给低速高压旋转设备的一种旋转接头，服务于加工中心旋转工作台、旋转平台、卷取机、转炉、大包回转工作台、液压机械及多通路高压控制器等设备。 DEWEL DRF06 Series are multi-way rotary joints designed to carry multiple media continuously for low-speed and high-pressure equipment. They are used on machining center revolving tables, rotating platforms, coiling machines, converters, ladle turret, hydraulic machinery, multi-way high pressure controller and etc.			



多通道旋转接头 Multi-Passage Rotary joint		 德威迩 www.sddeweier.com	
		TEL: +86 632 5822778 TEL: +86 632 5832779 E-mail: sddeweier88@163.com	
		P/N: DRF06020H10-G3/4"	