



80090DRF



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS		使用参数 Working parameters		
		介质 Fluid	压力 Pressure	温度 Temperature 转速 Rotating speed
MAX. PRESSURE	32MPa; <320Bar>	空气 Air	2.0MPa;	80℃ 40RPM
MAX. SPEED	250RPM;	水 Water	4.0MPa;	80℃ 30RPM
TEMPERATURE	-20℃----+80℃	液压油 Hydraulic oil	7.0MPa;	80℃ 30RPM
MEDIA TYPE 介质	Hydraulic oil/water/air		25MPa;	80℃ 20RPM
备注：技术参数数据为最大值，并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.		德威迩公司 DRF06H10 系列旋转接头是一种专门具有多个通道，可连续旋转多种介质高压旋转接头的一种旋转接头。服务于加工中心旋转工作台、旋转平台、卷取机、转炉、大包回转工作台、液压机械及多通道高压控制阀等设备。 DEWEL DRF06H10 Series are multi-way rotary joints designed to carry multiple media continuously for low-speed and high-pressure equipment. They are used on machining center revolving tables, rotating platforms, coiling machines, converters, ladle turret, hydraulic machinery, multi-way high pressure controller and etc.		



多通道旋转接头 Multi-Passage Rotary joint E-mail: sddeweier88@163.com		DEWEIER 德威迩 www.sddeweier.com	
TEL: +86 632 5822778 TEL: +86 632 5832779		P/N: DRF06008H10-G1/4"	