




S530-65X-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

技术参数 TECHNICAL PARAMETERS

使用参数 Working parameters

TECHNICAL PARAMETERS		介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
MAX. PRESSURE	2.0MPa; (20Bar)	蒸汽Steam	2.0MPa;	240℃	30RPM
MAX. SPEED	100RPM;	热油 Hot oil	4.0MPa;	280℃	30RPM
TEMPERATURE	-20℃----+280℃	Convex sealing design with sealing velocity 4 times higher than common structure. mized carbon guide separation to provide high stability for vibrant equipment. Anti-impurity structure for prolonged service life. High-temp-resistant alloy spring and antimony carbon rings for prolonged operation in			
MEDIA TYPE 介质	Steam/hot oil 蒸汽/热油等				

备注：技术参数数据为最大值,并不能同时使用;

The technical parameter data is the maximum value and cannot be used at the same time.

高温旋转接头
High temperature rotary joint
E-mail: sddeweier88@163.com

DEWEIER
德威迩

www.sddeweier.com



TEL : +86 632 5822778
TEL : +86 632 5832779

P/N : S530-65X-00F