



SS530-80X-00F



枣庄市德威迩机械科技有限公司

Dewel Machinery Technology Co., Ltd.

| 技术参数 TECHNICAL PARAMETERS | | 使用参数 Working parameters | | | |
|--|-----------------|---|-------------|----------------|-------------------|
| MAX. PRESSURE | 2.0MPa; (20Bar) | 介质 Fluid | 压力 Pressure | 温度 Temperature | 转速 Rotating speed |
| MAX. SPEED | 100RPM; | 蒸汽 Steam | 1.0MPa; | 240℃ | 15RPM |
| TEMPERATURE | -20℃-----+280℃ | 热油 Hot oil | 1.6MPa; | 280℃ | 15RPM |
| MEDIA TYPE 介质 | Steam/hot oil | Convex sealing design with sealing velocity 4 times higher than common structure. mized carbon guide separation to provide high stability for vibrant equipment. Anti-impurity structure for prolonged service life. High-temp-resistant alloy spring and antimony carbon rings for prolonged operation in hot oil application. Free from constant maintenance and lubrication, easy to repair. | | | |
| | 蒸汽/热油等 | | | | |
| 备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time. | | | | | |

高温旋转接头
 High temperature rotary joint
 E-mail: sddeweier88@163.com



TEL : +86 632 5822778
TEL : +86 632 5832779



DEWEER
德威迩

www.sddeweier.com

P/N: S530-80X-00F