




S530-25X-03F



枣庄市德威迩机械科技有限公司
Dewel Machinery Technology Co., Ltd.

| 技 术 参 数 TECHNICAL PARAMETERS | | 使 用 参 数 Working parameters | | | |
|--|-----------------|--|-------------|---------------|-------------------|
| MAX. PRESSURE | 2.0MPa; (20Bar) | 介质 Fluid | 压力 Pressure | 温度Temperature | 转速 Rotating speed |
| MAX. SPEED | 100RPM; | 蒸汽Steam | 2.0MPa; | 240℃ | 100RPM |
| TEMPERATURE | -20℃----+280℃ | 热油 Hot oil | 4.0MPa; | 280℃ | 100RPM |
| MEDIA TYPE 介 质 | Steam/hot oil | Convex sealing design with sealing velocity 4 times higher than common structure. mized carbon guide separation to provide high stability for vibrant equipment. Anti-impurity structure for prolonged service life. High-temp-resistant alloy spring and antimony carbon rings for prolonged operation in hot oil application. Free from constant maintenance and lubrication, easy to repair. | | | |
| | 蒸汽/ 热油等 | | | | |
| 备注：技术参数数据为最大值,并不能同时使用; The technical parameter data is the maximum value and cannot be used at the same time. | | | | | |

| | | |
|---|--|---|
| 高温旋转接头 High temperature rotary joint E-mail: sddeweier88@163.com | |  德威迩 www.sddeweier.com |
|  TEL : +86 632 5822778 TEL : +86 632 5832779 | | |