



S530-80X-03R



枣庄市德威迩机械科技有限公司
Dewel Machinery Technology Co., Ltd.

技 术 参 数 TECHNICAL PARAMETERS		使 用 参 数 Working parameters			
MAX. PRESSURE	2.0MPa; (20Bar)	介质 Fluid	压力 Pressure	温度Temperature	转速 Rotating speed
MAX. SPEED	100RPM;	蒸汽Steam	1.0MPa;	240℃	15RPM
TEMPERATURE	-20℃----+280℃	热油 Hot oil	1.6MPa;	280℃	15RPM
MEDIA TYPE 介 质	Steam/hot oil	Convex sealing design with sealing velocity 4 times higher than common structure. mized carbon guide separation to provide high stability for vibrant equipment. Anti-impurity structure for prolonged service life. High-temp-resistant alloy spring and antimony carbon rings for prolonged operation in hot oil application. Free from constant maintenance and lubrication, easy to repair.			
	蒸汽/ 热油等				
备注：技术参数数据为最大值,并不能同时使用； The technical parameter data is the maximum value and cannot be used at the same time.					

高温旋转接头
High temperature rotary joint
E-mail: sddeweier88@163.com

TEL : +86 632 5822778
TEL : +86 632 5832779

DEWEIER
德威迩
www.sddeweier.com

P/N : S530-80X-03R